

Spa Chilling System

.6 Horsepower
Smart Chilling System



FEATURES

- .6 HP Powerful Cooling (Min 37°F / 3°C)
- 1-3°F of Cooling Every 40 Minutes
- Heat Function (Max 80°F / 26°C)
- Wifi Enabled Mobile App Controlled
- 5" Touchscreen Digital Display
- 15-Micron Filtration (4.5" Replaceable Filter)
- Automated Ozone Sanitation
- Self-Priming High-Flow Rate Pump
- GFCI Protection
- Includes: Hose Kit, Filter Wrench, & Two Filter Cartridge Replacements
- Lockable Casters
- Steel Reinforced Inset Carrying Handles
- Quick Connect Fittings
- Overheating Protection
- Max Temperature Exposure 85°F
- Min Temperature Exposure 32°F
- 1 Year Warranty
- Weight: 50 lbs
- Dimensions (LxWxH): 17"x11"x19"

ELECTRICAL

Electrical Service: 120V/20amp/60Hz

NEMA 5-20R GFCI Outlet

610W / 5.1 AMPS



DCT-SY-06-HC



DYNAMIC
COLD THERAPY

Spa Chilling System

.8 Horsepower
Smart Chilling System



FEATURES

- .8 HP Powerful Cooling (Min 37°F / 3°C)
- 1-3°F of Cooling Every 30 Minutes
- Heat Function (Max 80°F / 26°C)
- Wifi Enabled Mobile App Controlled
- 5" Touchscreen Digital Display
- 15-Micron Filtration (10.5" Replaceable Filter)
- Automated Ozone Sanitation
- Self-Priming High-Flow Rate Pump
- GFCI Protection
- Includes: Hose Kit, Filter Wrench, & Two Filter Cartridge Replacements
- Lockable Casters
- Steel Reinforced Inset Carrying Handles
- Quick Connect Fittings
- Overheating Protection
- Max Temperature Exposure 90°F
- Min Temperature Exposure 32°F
- 1 Year Warranty
- Weight: 50 lbs
- Dimensions (LxWxH): 19"x14"x21"

ELECTRICAL

Electrical Service: 120V/20amp/60Hz

NEMA 5-20R GFCI Outlet

725W / 6.1 AMPS



DCT-SY-08-HC



DYNAMIC
COLD THERAPY

Spa Chilling System

1 Horsepower Smart Chilling System



FEATURES

- 1 HP Powerful Cooling (Min 37°F / 3°C)
- 1-3°F of Cooling Every 20 Minutes
- Heat Function (Max 80°F / 26°C)
- Wifi Enabled Mobile App Controlled
- 5" Touchscreen Digital Display
- 15-Micron Filtration (10.5" Replaceable Filter)
- Automated Ozone Sanitation
- Self-Priming High-Flow Rate Pump
- GFCI Protection
- Includes: Hose Kit, Filter Wrench, & Two Filter Cartridge Replacements
- Lockable Casters
- Steel Reinforced Inset Carrying Handles
- Quick Connect Fittings
- Overheating Protection
- Max Temperature Exposure 95°F
- Min Temperature Exposure 32°F
- 1 Year Warranty
- Weight: 50 lbs
- Dimensions (LxWxH): 22"x16"x22"

ELECTRICAL

Electrical Service: 120V/20amp/60Hz

NEMA 5-20R GFCI Outlet

1170W / 9.75 AMPS



DCT-SY-10-HC



DYNAMIC
COLD THERAPY