

AIPHONE SURFACE MOUNT VIDEO INTERCOM KIT WITH SMARTPHONE CONNECTIVITY

Aiphone's AI-JOS-1VW kit is a video intercom solution with a surface mount door station (JO-DV) which includes everything you need for an app-capable video intercom system. With the added feature of smartphone connectivity that can be accessed anywhere, this kit provides enhanced security. It features a 7 inch touch screen for your convenience and suits a variety of home and office applications.

- Large 7" touchscreen provides crisp, clear detail of your caller
- Answer and open your door from the on-site master or your mobile device
- Connect up to 8 smartphones or tablets per system
- On-site monitor ensures calls get answered or recorded
- Store calls with no added fees using onboard memory
- Increase call storage by adding a MicroSD card to the on-site monitor
- Watch recorded calls from the on-site master or on the mobile app
- Die-cast zinc vandal resistant surface mount video door intercom faceplate
- Video door intercom automatically activates white LED lights to see clearly at night
- Standard doorbells can be replaced to add security when seeing and speaking with visitors

Inside Monitor

- Model: JO-1MDW
- Video display: 7" TFT LCD touchscreen
- Mounting: Surface wall mount or desk mount with MCW-S stand
- Internal call recording: 10 calls max. at 10 seconds per call
- Memory expansion: Micro SDHC card slot, 32GB max.
- Call recording with max memory: 1,000 calls max. at 10 seconds per call
- Door release: N/O dry contact, 24V AC/DC, 500mA
- Communication style: Handsfree or PTT app
- Model: Intercom app type B
- Max per system: 8 devices
- Door release: In-app slider activates contacts at JO-1MDW
- 155mm x 209.6mm x 27mm



Video Door Station

- Model: JO-DV Power source: Supplied by inside monitor
- Camera: 1/4" colour CMOS
- Mounting: Surface wall mount using a 1 gang electrical box
- Faceplate material: Zinc die cast
- Enclosure rating: IP54
- Impact rating: IK08
- Communication style: Handsfree
- Wiring to master: 2-cond, low cap, non-shielded
- Max. wire distance: 50m (22AWG) 330" (18AWG)
- Dimensions 179mm x 98mm x 26.8 mm



Power Supply

- Model: PS-1820UL
- Power source: AC 100 - 240V 50/60Hz
- Power output: DC 18V 2A



Phone 0416041524