

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

### 1 Identification

- **Product identifier**
- **Trade name:** SF7500 SUPER FLEX URETHANE PRIMER
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Superflite, Inc.  
3701 Hwy 162  
GRANITE CITY, IL  
62040 USA
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



GHS09 Harmful

Harmful by inhalation and in contact with skin.  
Flammable.

- **Information concerning particular hazards for human and environment:**  
The product has to be labeled due to the calculation procedure of international guidelines.
- **Classification system:**  
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 2)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 1)

**· Code letter and hazard designation of product:****· Hazard-determining components of labeling:**

xylene

**· Risk phrases:**

Flammable.

Harmful by inhalation and in contact with skin.

**· Safety phrases:**

Keep out of the reach of children.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container to hazardous or special waste collection point.

**· Classification system:****· NFPA ratings (scale 0 - 4)****· HMIS-ratings (scale 0 - 4)****· Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

### 3 Composition/information on ingredients

**· Chemical characterization: Mixtures****· Description:** Mixture of the substances listed below with nonhazardous additions.**· Dangerous components:**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	25-50%
1330-20-7	xylene	10-25%
123-86-4	n-butyl acetate	10-25%
13463-67-7	titanium dioxide	10-25%
78-93-3	butanone	2.5-10%

(Contd. on page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

1332-58-7 Kaolin

(Contd. of page 2)

≤ 2.5%

### 4 First-aid measures

**· Description of first aid measures****· General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**· After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

**· After skin contact:** Generally the product does not irritate the skin.**· After eye contact:** Rinse opened eye for several minutes under running water.**· After swallowing:** If symptoms persist consult doctor.**· Information for doctor:**

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

**· Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

**· Extinguishing media****· Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.**· For safety reasons unsuitable extinguishing agents:** Water with full jet**· Special hazards arising from the substance or mixture** No further relevant information available.**· Advice for firefighters****· Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

**· Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**· Environmental precautions:** Do not allow to enter sewers/ surface or ground water.**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

**· Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

See Section 13 for disposal information.

(Contd. of page 3)

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

**Components with limit values that require monitoring at the workplace:****1330-20-7 xylene**PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
BEI**123-86-4 n-butyl acetate**PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppmREL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 710 mg/m<sup>3</sup>, 150 ppmTLV Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 713 mg/m<sup>3</sup>, 150 ppm**78-93-3 butanone**PEL Long-term value: 590 mg/m<sup>3</sup>, 200 ppm

(Contd. on page 5)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 4)

REL Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 590 mg/m<sup>3</sup>, 200 ppm

TLV Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
BEI

**1332-58-7 Kaolin**

PEL Long-term value: 15\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fraction

REL Long-term value: 10\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fraction

TLV Long-term value: 2\* mg/m<sup>3</sup>  
E; as respirable fraction

**· Ingredients with biological limit values:****1330-20-7 xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

**78-93-3 butanone**

BEI 2 mg/L  
Medium: urine  
Time: end of shift  
Parameter: MEK

· **Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**

 Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 5)

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

**R** Tightly sealed goggles

### 9 Physical and chemical properties

**· Information on basic physical and chemical properties****· General Information****· Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	White
<b>Odor:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

**· pH-value:** Not determined.

**· Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	124 °C (255 °F)

**· Flash point:** 27 °C (81 °F)

**· Flammability (solid, gaseous):** Not applicable.

**· Ignition temperature:** 370 °C (698 °F)

**· Decomposition temperature:** Not determined.

**· Auto igniting:** Product is not selfigniting.

**· Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**· Explosion limits:**

<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	7.5 Vol %

**· Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

**· Density at 20 °C (68 °F):** 1.36 g/cm<sup>3</sup> (11.349 lbs/gal)

**· Relative density** Not determined.

(Contd. on page 7)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 6)

- |   |  |
|---|--|
| · <b>Vapour density</b>                           | Not determined.                            |
| · <b>Evaporation rate</b>                         | Not determined.                            |
| · <b>Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.          |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.                            |
| · <b>Viscosity:</b>                               |  |
| <b>Dynamic:</b>                                   | Not determined.                            |
| <b>Kinematic:</b>                                 | Not determined.                            |
| · <b>Solvent content:</b>                         |  |
| <b>Organic solvents:</b>                          | 32.6 %                                     |
| <b>VOC content:</b>                               | 32.6 %                                     |
|   | Coating VOC 446.2 g/l / 3.72 lb/gl         |
|   | Material VOC 446.2 g/l / 3.72 lb/gl        |
| · <b>Solids content:</b>                          | 67.4 %                                     |
| · <b>Other information</b>                        | No further relevant information available. |

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

#### 1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 7)

Harmful

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	2B
1330-20-7	xylene	3
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO <sub>2</sub> )	1
· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 9)



## Safety Data Sheet acc. to OSHA HCS



Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 8)

### 14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	Paint
· IMDG, IATA	PAINT
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 9)

· UN "Model Regulation": UN1263, Paint, 3, III

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

78-93-3 butanone

100-41-4 ethylbenzene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

100-41-4 ethylbenzene

14808-60-7 Quartz (SiO<sub>2</sub>)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

78-93-3 butanone

I

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

A4

1330-20-7 xylene

A4

13463-67-7 titanium dioxide

A4

1332-58-7 Kaolin

A4

77-58-7 dibutyltin dilaurate

A4

(Contd. on page 11)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 10)

100-41-4	ethylbenzene	A3
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO <sub>2</sub> )	

**· Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

**· Hazard symbols:****· Hazard-determining components of labeling:**

xylene

**· Risk phrases:**

Flammable.

Harmful by inhalation and in contact with skin.

**· Safety phrases:**

Keep out of the reach of children.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container to hazardous or special waste collection point.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Mr. Roberts

· **Date of preparation / last revision** 04/22/2015 / -

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF7500 SUPER FLEX URETHANE PRIMER**

(Contd. of page 11)

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*Flam. Liq. 3: Flammable liquids, Hazard Category 3*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Carc. 2: Carcinogenicity, Hazard Category 2*

USA