

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

1 Identification

- · Product identifier
- · Trade name: SF7870 MEDIUM REDUCER
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Superflite, Inc. 3701 Hwy 162

GRANITE CITY, IL

62040 USA

- · Information department: Product safety department
- · Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Harmful by inhalation and if swallowed. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Irritating to eyes and skin.



flammableHighly

flammable.



Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 1)

- · Information concerning particular hazards for human and environment:
- The product has to be labeled due to the calculation procedure of international guidelines.
- · Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- \cdot Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:





Harmful Highly flammable

· Hazard-determining components of labeling:

toluene

heptan-2-one

· Risk phrases:

Highly flammable.

Harmful by inhalation and if swallowed.

Irritating to eyes and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

· Safety phrases:

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)



Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 2)

· **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
110-43-0	heptan-2-one	25-50%
78-93-3	butanone	25-50%
108-88-3	toluene	10-25%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 3)

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

(Contd. on page 5)



Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 4) 78-93-3 butanone PEL Long-term value: 590 mg/m³, 200 ppm REL Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm TLV Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm 108-88-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift REL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm TLV Long-term value: 75 mg/m³, 20 ppm · Ingredients with biological limit values: 78-93-3 butanone BEI 2 mg/L Medium: urine Time: end of shift Parameter: MEK 108-88-3 toluene BEI 1.2 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene $1.3 \, mg/L$ Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

(Contd. on page 6)



Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 5)

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/the preparation.

Not determined.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

· pH-value:

Form: Liquid Color: Clear

Odor: CharacteristicOdour threshold: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:79 °C (174 °F)

• Flash point: $-4 \, ^{\circ}C \, (25 \, ^{\circ}F)$

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 7)



Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

	(Contd. of page
· Ignition temperature:	514 °C (957 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.0 Vol %
Upper:	11.5 Vol %
Vapor pressure at 20 °C (68 °F):	105 hPa (79 mm Hg)
Density at 20 °C (68 °F):	0.82307 g/cm³ (6.869 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.0 %
	Coating VOC 825.5 g/l / 6.88 lb/gl
	Material VOC 825.5 g/l / 6.88 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

10.4



Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 7)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification:				
110-43-0 heptan-2-one				
Oral	LD50	1670 mg/kg (rat)		
Dermal	LD50	12600 mg/kg (rabbit)		
108-88-3 to	108-88-3 toluene			
Oral	LD50	5000 mg/kg (rat)		
Dermal	LD50	12124 mg/kg (rabbit)		
Inhalative	LC50/4 h	5320 mg/l (mouse)		

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (I	International	Agency fo	or Research	h on Cancer)
-----------	---------------	-----------	-------------	--------------

108-88-3 toluene

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)



Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 8)

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	***************************************	
DOT, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT		
201		
Class	3 Flammable liquids	
Label	3	
IMDG, IATA		
IMDO, IATA		
dc		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, IMDG, IATA	II	
Environmental hazards: Marine pollutant:	No	

USz



Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 9)

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler): 33
EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot DOT$

• Quantity limitations On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

παλιπαίπ πει φααπιίγ ρεί σαιεί ραεκαξί

· UN "Model Regulation": UN1263, Paint, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3 butanone

108-88-3 toluene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 10)

· Carcinogenic categories

· EPA (En	vironmental Protection Agency)	
78-93-3	butanone	I
108-88-3	toluene	II
· TLV (Thi	reshold Limit Value established by ACGIH)	
108-88-3	toluene	A4
· NIOSH-C	Ca (National Institute for Occupational Safety and Health)	1
None of th	he ingredients is listed.	

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:





Harmful Highly flammable

· Hazard-determining components of labeling:

toluene

heptan-2-one

· Risk phrases:

Highly flammable.

Harmful by inhalation and if swallowed.

Irritating to eyes and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

· Safety phrases:

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Roberts
- · Date of preparation / last revision 04/22/2015 / -

(Contd. on page 12)



Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015 Reviewed on 04/22/2015

Trade name: SF7870 MEDIUM REDUCER

(Contd. of page 11)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

USA