

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

### 1 Identification

- **Product identifier**
- **Trade name:** SF820 FAST DRY CATALYST
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Superflite, Inc.  
3701 Hwy 162  
GRANITE CITY, IL  
62040 USA
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



GHS05 Corrosive

Irritating to eyes.



GHS02 Highly

flammable Highly  
flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labeled due to the calculation procedure of international guidelines.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 2)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 1)

**Code letter and hazard designation of product:****Risk phrases:**

Highly flammable.  
Irritating to eyes.

**Safety phrases:**

Keep out of the reach of children.  
Keep container in a well-ventilated place.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
If swallowed, seek medical advice immediately and show this container or label.

**Classification system:****NFPA ratings (scale 0 - 4)****HMIS-ratings (scale 0 - 4)****Other hazards****Results of PBT and vPvB assessment**

- PBT:** Not applicable.
- vPvB:** Not applicable.

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Description:** Mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%
67-64-1	acetone	10-25%
112926-00-8	Precipitated silica (Silica-Amorphous)	2.5-10%
110-43-0	heptan-2-one	2.5-10%

USA

(Contd. on page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 2)

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 3)

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**67-64-1 acetone**

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m<sup>3</sup>, (750) NIC-500 ppm

Long-term value: (1188) NIC-594 mg/m<sup>3</sup>, (500) NIC-250 ppm

BEI

**112926-00-8 Precipitated silica (Silica-Amorphous)**

PEL 20mppcf or 80mg/m<sup>3</sup> /%SiO<sub>2</sub>

REL Long-term value: 6 mg/m<sup>3</sup>

See Pocket Guide App. C

TLV TLV withdrawn

**110-43-0 heptan-2-one**

PEL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

REL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 233 mg/m<sup>3</sup>, 50 ppm

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 4)

**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:***Keep away from foodstuffs, beverages and feed.**Immediately remove all soiled and contaminated clothing.**Wash hands before breaks and at the end of work.**Avoid contact with the eyes.**Avoid contact with the eyes and skin.***· Breathing equipment:***In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.**Use suitable respiratory protective device in case of insufficient ventilation.***· Protection of hands:***The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.**Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.**Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation***· Material of gloves***The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.***· Penetration time of glove material***The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.***· Eye protection:****R** *Tightly sealed goggles*

### 9 Physical and chemical properties

**· Information on basic physical and chemical properties****· General Information****· Appearance:****Form:** *Liquid***Color:** *Whitish***· Odor:** *Characteristic***· Odour threshold:** *Not determined.***· pH-value:** *Not determined.***· Change in condition****Melting point/Melting range:** *Undetermined.***Boiling point/Boiling range:** *55 °C (131 °F)*

(Contd. on page 6)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 5)

· <b>Flash point:</b>	-17 °C (1 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	465 °C (869 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	2.6 Vol %
<b>Upper:</b>	13.0 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	233 hPa (175 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.09 g/cm <sup>3</sup> (9.096 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	28.2 %
<b>VOC content:</b>	15.6 %
	Coating VOC 264.0 g/l / 2.20 lb/gl
	Material VOC 170.2 g/l / 1.42 lb/gl
<b>Solids content:</b>	49.6 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 7)

USA

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 6)

**Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

**Information on toxicological effects****Acute toxicity:****Primary irritant effect:****on the skin:** No irritant effect.**on the eye:** Irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

112926-00-8 Precipitated silica (Silica-Amorphous)

3

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

**Toxicity****Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Behavior in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

USA

(Contd. on page 8)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015



**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 7)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |   |
|---|---|
| · <b>UN-Number</b><br>· <b>DOT, IMDG, IATA</b>  | UN1263  |
| · <b>UN proper shipping name</b><br>· <b>DOT</b><br>· <b>IMDG, IATA</b>                         | Paint<br>PAINT                                      |
| · <b>Transport hazard class(es)</b><br>· <b>DOT</b>   |   |
|              |   |
| · <b>Class</b><br>· <b>Label</b>  | 3 Flammable liquids<br>3                            |
| · <b>IMDG, IATA</b>   |   |
|              |   |
| · <b>Class</b><br>· <b>Label</b>  | 3 Flammable liquids<br>3                            |
| · <b>Packing group</b><br>· <b>DOT, IMDG, IATA</b>  | II  |
| · <b>Environmental hazards:</b><br>· <b>Marine pollutant:</b>                                   | No  |
| · <b>Special precautions for user</b><br>· <b>Danger code (Kemler):</b><br>· <b>EMS Number:</b> | Warning: Flammable liquids<br>33<br>F-E, <u>S-E</u> |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>                | Not applicable.                                     |

(Contd. on page 9)

USA



## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 8)

**· Transport/Additional information:**

**· DOT**

**· Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

**· IMDG**

**· Limited quantities (LQ)**

5L

**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· UN "Model Regulation":**

UN1263, Paint, 3, II

### 15 Regulatory information

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

**· Sara**

**· Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**· Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**· TSCA (Toxic Substances Control Act):**

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

67-64-1 acetone

110-43-0 heptan-2-one

**· Proposition 65**

**· Chemicals known to cause cancer:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

67-64-1 acetone

I

**· TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

(Contd. on page 10)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/22/2015

Reviewed on 04/22/2015

**Trade name: SF820 FAST DRY CATALYST**

(Contd. of page 9)

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

**· Hazard symbols:****· Risk phrases:**

Highly flammable.

Irritating to eyes.

**· Safety phrases:**

Keep out of the reach of children.

Keep container in a well-ventilated place.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

If swallowed, seek medical advice immediately and show this container or label.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing SDS:** Environment protection department.**· Contact:** Mr. Roberts**· Date of preparation / last revision** 04/22/2015 / -**· Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A