



Load Switching Devices

SEHAZB-SWITCH-MTR /
SEHAZB-SCKT-MTR-XX /
SEHAZB-DR-SWITCH-2



▶ AC Switch with Meter

▶ Dry Contact Switch



▶ Plug-In Socket with Meter

DEVICE CONTROL

Maximize self-consumption by controlling device usage

AC Switch with Meter | Plug-In Socket with Meter

- Wireless AC switch for controlling electrical devices
- Device control can be done remotely according to a pre-configured schedule or dynamically by the inverter for maximized self-consumption
- Built-in energy and power consumption metering
- Provides power measurements up to 3kW

Dry Contact Switch

- Wireless dry contact switch for controlling electrical devices
- Suitable for heat pump control
- Supports a wide input voltage range

	SEHAZB-SWITCH-MTR AC Switch with Meter	SEHAZB-SCKT-MTR-XX * Plug-In Socket with Meter	SEHAZB-DR-SWITCH-2 Dry Contact Switch	Units
ELECTRICAL SERVICE				
Operating Voltage Range - Line to Neutral	90 - 250			Vac
AC Frequency	50/60			Hz
Maximum Active Power Measurement	3	N/A		kW
Maximum Load Current	13			A
Dry Contact Voltage Range	N/A	0 - 250		Vac/Vdc
COMMUNICATION				
Supported Communication Protocol	ZigBee Home Automation			
Nominal Transmit Power	3	10		dBm
Operating Frequency Range	2.4 - 2.5			GHz
Outdoor (LOS) Range	100	400		m
Indoor Range**	50			m
STANDARD COMPLIANCE				
Radio	ETSI EN 300 328 V 1.8.1, ETSI EN 301 489-1, ETSI EN 301 489-17		ETSI EN 300 328 V 1.8.1, ETSI EN 301 489-1, ETSI EN 301 489-17 ***	
Safety	EN 60335-1, EN 60335- 2-30, EN 50371	EN 60950-1, EN 50371	EN 60335-1, EN 60335- 2-30, EN 50371 ***	
Immunity	EN 55014-2	EN 61000-6-2	EN 55014-2 ***	
Emissions	EN 55014-1, EN 61000- 3-2, EN 61000-3-3	EN 61000-6-3	EN 55014-1, EN 61000- 3-2, EN 61000-3-3 ***	
INSTALLATION SPECIFICATIONS				
Operating Temperature Range	0 to +50			°C
Protection Rating	IP30			
Dimensions (H x W x D)	110 x 70 x 25	110 x 50 x 40	110 x 70 x 25	mm
Mounting Type	Wall mount	N/A	Wall mount	

* Multiple plug types for various sockets:

XX = GB, DE, FR, IT

** Approximate values. May differ depending on specific installation conditions

*** Pending.

