


DS18[®]

OWNER'S MANUAL
MANUAL DE USUARIO

PRO-GM6SE

**6.5" SEALED BACK
MID-RANGE LOUDSPEAKER**




ALTAVOZ DE 6.5" DE RANGO MEDIO
SELLADO ATRÁS



ENGLISH | ESPAÑOL



PRO-GM6SE





SPECIFICATIONS / ESPECIFICACIONES:

Nominal Diameter / Diámetro Nominal.....	6.5" / 165.1mm
Nominal Impedance / Impedancia Nominal	8 OHMS
RMS Power Handling / Manejo de Potencia RMS.....	140 Watts
MAX Power Handling / Manejo de Potencia MAX.....	480 Watts
Sensitivity / Sensibilidad (1w/1m).....	93dB
Frequency Response / Respuesta de Frecuencia.....	315Hz-10KHz
Recommended Hi Pass Crossover / Crossover de Paso Alto Recomendado	400 Hz
Pair or single / Par o Unidad.....	Single / Unidad

MOTOR / MOTOR:

Voice Coil Diameter / Diámetro de la Bobina de Voz	1.5" / 38.1mm
Voice Coil Former Material / Material Interior de Bobina Móvil	Kapton
Winding Material / Material de Bobinado	CCAW
Cone Material / Material del Cono	Paper / Papel
Dustcap Material / Material de la Tapa anti-Polvo.....	Paper / Papel
Surround Material / Material de la Suspensión.....	Cloth / Tela
Basket Material / Material de la Canasta.....	Steel / Acero
Basket Color / Color de Canasta.....	Matte Black / Negro Mate
Magnet Material / Material del Imán	Ferrite / Ferrita
Magnet Weight / Peso del Imán	23 oz

THIELE & SMALL PARAMETERS / PARÁMETROS T/S:

Equivalent Volume / Volumen Equivalente	Vas	0.48L / 0.017ft3
Free Air Resonance / Resonancia al Aire Libre	Fs	457Hz
Mechanical Factor / Factor Mecánico	Qms	7.744
Electrical Factor / Factor Eléctrico.....	Qes	3.592
Total Factor / Factor Total	Qts	2.454
Mechanical Mass / Masa en Movimiento	Mms.....	6.187g
Mechanical Compliance / Cumplimiento Mecánico	Cms	0.02mm/N
BL Factor / Factor BL	BL	5.54
Voice Coil Inductance / Inductancia de Bobina de Voz	Le.....	0.689mH
Cone Area / Área del Cono	Sd	132.73cm2
DC Resistance / Resistencia DC.....	Re.....	6.2 ohm

MEASUREMENTS / MEDIDAS:

Overall Diameter / Diámetro Total.....	6.57" / 167mm
Overall Depth / Profundidad Total.....	2.7" / 69mm
Front Mount Baffle Cutout / Corte del Orificio de Montaje	5.7" / 145 mm
Mounting Depth / Profundidad de Montaje.....	2.5" / 64mm
Motor Diameter / Diámetro del Motor	4.33" / 110mm



FOR MORE INFORMATION
PLEASE VISIT
DS18.COM

WE LIKE IT LOUD

The DS18 logo, featuring a stylized red graphic element on the left that resembles a lightning bolt or a curved line, followed by the text "DS18" in a bold, italicized, sans-serif font. A registered trademark symbol (®) is located at the top right of the "8".

DS18[®]