

### Function Description

- Large LCD display
- With input and output indicators
- Three operating modes: ON/OFF/AUTO
- With Ni-MH rechargeable battery
- Min. Setting Time: 1 minute
- Max. Setting Time: 7 days
- With daylight saving time option
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10 C to 50 C)
- Storage Temperature: -4 °F to 140°F (-20 C to 60 C)



### Input & Output Appearance

8x




### Ratings & Approval

**Voltage Compatibility:** 125V AC

**Frequency:** 60Hz

**Max. Load:** 15A/1875W Resistive  
10A/1875W Tungsten

**Other Ratings:** 1/2 HP



### Packing



Product Measurement (inch): 3.58×1.71×11.59

Product Weight (lb): 1.59

Unit Package Measurements (inch): 4.18×2.99×12.00

Unit Package Weight (lb): 1.62

Master Carton Measurements (inch): 21.65×14.45×13.07

Master Carton Weight (lbs): 34.35

Master Carton Quantity: 20 PCS

Master Carton Cube (cu.ft): 2.37

#### BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730

Customer Service Assistance: 1.909.592.1881

E-mail: [support@bn-link.com](mailto:support@bn-link.com)

[Http://www.bn-link.com](http://www.bn-link.com)

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China