

## Function Description

- With overload protection
- With surge protection
- With input, output and surge indicators
- With ON/Timer slide switch
- Up to 48 on/off programs daily
- Min. Setting Time: 15 minutes
- Max. Setting Time: 24 hours
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10 C to 50 C)
- Storage Temperature: -4 °F to 140°F (-20 C to 60 C)



## Input & Output Appearance

8x



## Ratings & Approval

**Voltage Compatibility:** 125V AC  
**Frequency:** 60Hz  
**Max. Load:** 15A/1875W Resistive  
**Other Ratings:** Type 3 SPD,  
 VPR:800V(L-N)(L-G)(N-G)



## Packing



Product Measurement (inch): 3.58×1.72×11.59  
 Product Weight (lb): 1.50  
 Unit Package Measurements (inch): 4.18×2.99×12.00  
 Unit Package Weight (lb): 1.54  
 Master Carton Measurements (inch): 21.65×14.45×13.07  
 Master Carton Weight (lbs): 34.33  
 Master Carton Quantity: 20 PCS  
 Master Carton Cube (cu.ft): 2.37

**CENTURY PRODUCTS INC.**  
 3545 Granada Ave El Monte Ca 91731  
 Custom Service Assistance: 1.909.592.1881  
 E-mail: support@bn-link.com  
 Http://www.bn-link.com  
 Hours: 9AM - 5PM PST, Mon - Fri  
 Designed in California Made in Cambodia