

## **Easy Digital Timer** BND-60/U132

- BN=LINK®

- AM/PM display

- Min. Setting time: 1 minute - Max. Setting time: 24 hours

- Operating Temperature: 14°F to 122°F (-10 C to 50 C)
   Storage Temperature: -4 °F to 140°F (-20 C to 60 C)

**Input & Output** 

Ratings & Approval

Frequency: 60Hz Max. Load: 15A/1875W Resistive 8A/1000W Tungsten Other Ratings: 1/3 HP

**Packing** 

EASY SET 24 HOUR TIMER

Voltage Compatibility: 125V AC

1 OFF 2000 SETTIME PROG T - HUL-UST

Appearance

- Operating environment: for indoor use only

- With daylight saving time function - With Ni-MH rechargeable battery
- Up to 2 ON/OFF programs daily
- **Function Description**

off PM

G + - RCL-DST

Product Measurement (inch): 2.99×2.13×1.57

Unit Package Measurements (inch): 4.02×3.27×1.99

Master Carton Measurements (inch): 17.05×10.83×8.74

Product Weight (lbs): 0.16

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730
Customer Service Assistance: 1.909.592.1881
E-mail: support@bn-link.com
Http://www.bn-link.com
Hours: 9AM-5PM PST, Mon - Fri
Designed in California Made in China

Unit Package Weight (lbs): 0.4

Master Carton Weight (lbs): 21.57 Master Carton Quantity: 50 PCS Master Carton Cube (cu.ft): 0.93

1x 🕌