

Function Description

- Dual outlets
- Photocell Sensor Mode
- 7 positions: ON, OFF, 2/4/6/8-hour countdown, dusk-dawn.
- Operating environment: for outdoor use
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)
- Storage Temperature: -4 °F to 140°F (-20°C to 60°C)



Input & Output Appearance



Ratings & Approval

Voltage Compatibility : 125V AC
Frequency : 60Hz
Max. Load : 15A/1875W Resistive
 5A/625W Tungsten



Packing



Product Measurement (inch): 3.86×1.97×6.34
 Product Weight (lb): 0.43
 Unit Package Measurements (inch): 3.86×1.97×6.34
 Unit Package Weight (lb): 0.5
 Master Carton Measurements (inch): 20.08×11.1×13.43
 Master Carton Weight (lbs): 26.90
 Master Carton Quantity: 50 PCS
 Master Carton Cube (cu.ft): 1.73

BN-LINK INC.
 11701 6th Street, Rancho Cucamonga, CA 91730
 Customer Service Assistance: 1.909.592.1881
 E-mail: support@bn-link.com
 Http://www.bn-link.com
 Hours: 9AM - 5PM PST, Mon - Fri
 Designed in California Made in China