

Function Description

- Easy to use
- Up to 8 On/Off programs daily
- Min. Setting: 1 minute
- Max. Setting: 7 days
- Fully insert pin
- Operating environment: For indoor/outdoor use
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)
- Storage Temperature: -4 °F to 140°F (-20°C to 60°C)



Input & Output Appearance

2x



Ratings & Approval

Voltage Compatibility : 125V AC**Frequency :** 60Hz**Max. Load :** 15A/1875W Resistive

15A/1875W General Purpose

Other Ratings: 1/2 HP**Power Cord:** 14/3 SJTW

Packing



Product Measurement (inch): 4.49×2.36×5.28

Product Weight (lb): 0.52

Unit Package Measurements (inch): 4.49×2.36×5.28

Unit Package Weight (lb): 0.66

Master Carton Measurements (inch): 18.90×13.11×11.65

Master Carton Weight (lbs): 26

Master Carton Quantity: 40 PCS

Master Carton Cube (cu.ft): 1.67

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730

Customer Service Assistance: 1.909.592.1881

E-mail: support@bn-link.com

Http://www.bn-link.com

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China