

Function Description

- With ON/Timer override switch
- Up to 48 On/Off programs daily
- Min. Setting: 15 minutes
- Max. Setting: 24 hours
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10 C to 50 C)
- Storage Temperature: -4 °F to 140°F (-20 C to 60 C)



Input & Output Appearance

1x 

Ratings & Approval

Voltage Compatibility: 125V AC**Frequency:** 60Hz**Max. Load:** 15A/1875W Resistive
15A/1875W Tungsten**Other Ratings:** 1/2 HP

Packing



Product Measurement (inch): 2.93×3.01×4.77

Product Weight (lb): 0.34

Unit Package Measurements (inch): 4.84×3.11×5.14

Unit Package Weight (lb): 0.78

Master Carton Measurements (inch): 15.94×14.96×11.22

Master Carton Weight (lbs): 27.35

Master Carton Quantity: 30 PCS

Master Carton Cube (cu.ft): 1.55

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730

Customer Service Assistance: 1.909.592.1881

E-mail: support@bn-link.com

Http://www.bn-link.com

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China