

## Function Description

- With ON/Timer override switch
- Up to 48 On/Off programs daily
- Min. Setting: 15 minutes
- Max. Setting: 24 hours
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10 C to 50 C)
- Storage Temperature: -4 °F to 140°F (-20 C to 60 C)



## Input & Output Appearance

1x 

## Ratings & Approval

- Voltage Compatibility:** 125V AC  
**Frequency:** 60Hz  
**Max. Load:** 15A/1875W Resistive  
 15A/1875W Tungsten  
**Other Ratings:** 1/2 HP



## Packing



- Product Measurement (inch): 3.31×2.99×5.16  
 Product Weight (lb): 0.295  
 Unit Package Measurements (inch): 3.31×2.99×5.16  
 Unit Package Weight (lb): 0.37  
 Master Carton Measurements (inch): 16.73×15.55×11.14  
 Master Carton Weight (lbs): 20.26  
 Master Carton Quantity: 50 PCS  
 Master Carton Cube (cu.ft): 1.68

**BN-LINK INC.**  
 11701 6th Street, Rancho Cucamonga, CA 91730  
 Customer Service Assistance: 1.909.592.1881  
 E-mail: support@bn-link.com  
 Http://www.bn-link.com  
 Hours: 9AM - 5PM PST, Mon - Fri  
 Designed in California Made in China