

Function Description

- With ON/Timer override switch
- Up to 48 On/Off programs daily
- Min. Setting: 15 minutes
- Max. Setting: 24 hours
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)



Input & Output Appearance

2x



Ratings & Approval

Voltage Compatibility: 125V AC

Frequency: 60Hz

Max. Load: 15A/1875W Resistive

15A/1875W Tungsten

Other Ratings: 1/2 HP



Packing



Product Measurement (inch): 3.50×3.43×3.05

Product Weight (lb): 0.39

Unit Package Measurements (inch): 3.62×3.58×3.39

Unit Package Weight (lb): 0.25

Master Carton Measurements (inch): 18.70×18.70×7.68

Master Carton Weight (lbs): 25.35

Master Carton Quantity: 50 PCS

Master Carton Cube (cu.ft): 1.55

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730

Customer Service Assistance: 1.909.592.1881

E-mail: support@bn-link.com

Http://www.bn-link.com

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China