

Function Description

- Easy to use
- 4 countdown functions (2/4/6/8 hours)
- IP44 Waterproof
- Light sensor timer
- 2 switch functions (always on/off)
- Operating environment: for outdoor use
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)
- Storage Temperature: -4 °F to 140°F (-20°C to 60°C)



Input & Output Appearance

2x



Ratings & Approval

- Voltage Compatibility :** 125V AC
- Frequency :** 60Hz
- Max. Load :** 15A/1875W Resistive
10A/1250W Tungsten and Ballast
- Other Ratings:** 1/2 HP



Packing



- Product Measurement (inch): 3.43×2.64×5.67
- Product Weight (lb): 0.36
- Unit Package Measurements (inch): 3.43×2.64×5.67
- Unit Package Weight (lb): 0.44
- Master Carton Measurements (inch): 17.95×11.34×12.28
- Master Carton Weight (lbs): 18.78
- Master Carton Quantity: 40 PCS
- Master Carton Cube (cu.ft): 1.45

BN-LINK INC.
11701 6th Street, Rancho Cucamonga, CA 91730
Customer Service Assistance: 1.909.592.1881
E-mail: support@bn-link.com
Http://www.bn-link.com
Hours: 9AM - 5PM PST, Mon - Fri
Designed in California Made in China