

### Function Description

- Easy set push buttons with LED indicators
- Preset countdown programs :5/15/30/ minutes,1/2/4 hours
- Manual ON/OFF button
- Program runs once or repeats daily
- Operating environment: for indoor use only
- Operating Temperature: 5°F to 122°F (-15°C to 50°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)



### Input & Output Appearance

Connect to fixed wiring with Close-terminal



### Ratings & Approval

**Voltage Compatibility:** 125V AC

**Frequency:** 60Hz

**Max. Load:** 15A/1875W Resistive

10A/1250W Tungsten

10A/1250W Ballast

**Other:** 1/2 HP,TV-5



### Packing



Product Measurement (inch): 2.87x2.17x4.72

Product Weight (lb): 0.21

Unit Package Measurements (inch): 2.87x2.17x4.72

Unit Package Weight (lb): 0.34

Master Carton Measurements (inch): 15.16x12.20x10.43

Master Carton Weight (lbs): 18.41

Master Carton Quantity: 50 PCS

Master Carton Cube (cu.ft): 1.12

**BN-LINK INC.**  
 11701 6th Street, Rancho Cucamonga, CA 91730  
 Customer Service Assistance: 1.909.592.1881  
 E-mail: support@bn-link.com  
 Http://www.bn-link.com  
 Hours: 9AM - 5PM PST, Mon - Fri  
 Designed in California Made in China