

Function Description

- Suitable to refrigeration systems
- LED display
- °C or °F display
- Temperature probe can sense between: 0 – 60° C (32-140 °F)
- Temperature control range: 5 – 42° C (40 -108 °F)
- Display accuracy: 0.1 C/°F
- Temperature setting interval: 1 C/°F
- Program auto-saving in power cut-off
- Operating environment: for indoor use
- Operating Temperature: 14 °F to 122 °F (-10 C to 50 C)
- Storage Temperature: -4 °F to 140 °F (-20 C to 60 C)



Input & Output Appearance

1x



Ratings & Approval

Voltage Compatibility : 120V AC

Frequency : 60Hz

Max. Load : 8.3A/1000W



Packing



Product Measurement (inch): 3.15×2.91×7.32

Product Weight (lb): 0.68

Unit Package Measurements (inch): 3.15×2.91×7.32

Unit Package Weight (lb): 0.78

Master Carton Measurements (inch): 17×15.60×9.76

Master Carton Weight (lbs): 24.97

Master Carton Quantity: 30 PCS

Master Carton Cube (cu.ft): 1.50

BN-LINK INC.
 11701 6th Street, Rancho Cucamonga, CA 91730
 Customer Service Assistance: 1.909.592.1881
 E-mail: support@bn-link.com
 Http://www.bn-link.com
 Hours: 9AM - 5PM PST, Mon - Fri
 Designed in California Made in China