

Function Description

- Suitable to heating systems
- LED display
- °C or °F display
- Temperature display range: 0 – 60 °C (32-140 °F)
- Temperature control range: 5 – 42 °C (40 -108 °F)
- Display accuracy: 0.1 °C/°F
- Temperature setting interval: 1 °C/°F
- Program auto-saving in power cut-off
- Operating environment: for indoor use
- Operating Temperature: 14 °F to 122 °F (-10 °C to 50 °C)
- Storage Temperature: -4 °F to 140 °F (-20 °C to 60 °C)



Input & Output Appearance

1x



Ratings & Approval

Voltage Compatibility: 120V AC

Frequency: 60Hz

Max. Load: 8.3A/1000W



Packing



- Product Measurement (inch): 3.15×3.00×7.28
- Product Weight (lb): 0.67
- Unit Package Measurements (inch): 3.15×3.00×7.28
- Unit Package Weight (lb): 0.76
- Master Carton Measurements (inch): 17.09×15.47×9.84
- Master Carton Weight (lbs): 24.75
- Master Carton Quantity: 30 PCS
- Master Carton Cube (cu.ft): 1.50

BN-LINK INC.
 11701 6th Street, Rancho Cucamonga, CA 91730
 Customer Service Assistance: 1.909.592.1881
 E-mail: support@bn-link.com
 Http://www.bn-link.com
 Hours: 9AM - 5PM PST, Mon - Fri
 Designed in California Made in China