

### Function Description

- Sunrise/sunset activation
- Large LCD display
- AM/PM clock display
- With ON/OFF/Timing shift function
- With Ni-MH rechargeable battery
- Program: up to 18 ON/OFF daily; Min. Setting: 1 minute, Max. Setting: 7 days
- Operating environment: for indoor use only
- Operating Temperature: 5°F to 122°F (-15°C to 50°C)
- Storage Temperature: -4 °F to 140°F (-20°C to 60°C)



### Input & Output Appearance

Connect to fixed wiring with Close-terminal



### Ratings & Approval

**Voltage Compatibility :** 125V AC

**Frequency :** 60Hz

**Max. Load :** 15A/1875W Resistive

10A/1250W Tungsten

10A/1250W Ballest

**Other Ratings:** 1/2 HP, TV-5



### Packing



Product Measurement (inch): 3.15×2.32×4. 88

Product Weight (lb): 0.23

Unit Package Measurements (inch): 3.15×2.32×4. 88

Unit Package Weight (lb): 0.57

Master Carton Measurements (inch): 16.22×12.64×10.67

Master Carton Weight (lbs): 18.69

Master Carton Quantity: 50 PCS

Master Carton Cube (cu.ft): 1.27

#### BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730  
 Customer Service Assistance: 1.909.592.1881  
 E-mail: support@bn-link.com  
 Http://www.bn-link.com  
 Hours: 9AM - 5PM PST, Mon - Fri  
 Designed in California Made in China