

## 6-outlet Countdown Timer with Touch Sensor and Ground Stake **BNC-60/U13R**

#### **Function Description**

- 7 indicators : ON, OFF, 2/4/6/8-hour countdown, dusk-dawn
- With output indicator
- Remote control range: 80 ft(open space)
- With overloading protectorOperating environment: for outdoor use



### Input & Output Appearance

6x 🕌



## **Ratings & Approval**

#### **Outlet:**

Voltage Compatibility: 125V AC Frequency: 60Hz Max. Load: 15A/1875W Resistive 8A/1000W Tungsten Other Ratings: 1/2 HP

#### **Remote Controller:**

Wireless Frequency: 433.92 MHz Battery Type: 12V 23A









Product Measurement (inch): 5.20×4.33×9.69 Product Weight (lb): 1.33 Ú¦[å`&qÜ^{ [c^ÁÔ[}d[|DÁT ^æ` \^{ ^} dG] &@DA5.20×4.33×9.69  $\dot{U} [ a^* \& d c U^{2} [ c^{A} \hat{O} [ ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^{2} ] d [ | D \hat{V} ^{2} a^{B} c A C U^$ Unit Package Measurements (inch): 5.24×4.39×9.69Á Unit Package Weight (lb): 1.65 Master Carton Measurements (inch): 21.20×10.52×9.81Á Master Carton Weight (lbs): 15.11 Master Carton Quantity: 8 PCS Master Carton Cube (cu.ft): 1.27

# BN-LINK INC. 11701 6th Street, Rancho Cucamonga, CA 91730 Customer Service Assistance: 1.909.592.1881 E-mail: support@bn-link.com Http://www.bn-link.com Http://www.bn-link.com Hours: 9AM - 5PM PST, Mon - Fri Designed in California Made in China