

Function Description

- Easy set push buttons
- Min. Setting time: 15 minutes
- Max. Setting time: 6 hours
- With output indicator
- With grounded pin
- Program runs once or repeats daily
- Operating environment: for indoor use only
- Operating Temperature: 5°F to 122°F (-15°C to 50°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)



Input & Output Appearance

1x



Ratings & Approval

Voltage Compatibility : 125V AC

Frequency : 60Hz

Max. Load : 15A/1875W Resistive

10A/1250W Tungsten

10A/1250W Ballast

Other Ratings: 1/2 HP, TV-5



Packing



Product Measurement (inch): 2.95×2.36×2.56

Product Weight (lb): 0.18

Unit Package Measurements (inch): 2.95×2.36×2.56

Unit Package Weight (lb): 0.23

Master Carton Measurements (inch): 15.24×12.99×11.14

Master Carton Weight (lbs): 24.11

Master Carton Quantity: 100 PCS

Master Carton Cube (cu.ft): 1.28

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730
 Customer Service Assistance: 1.909.592.1881
 E-mail: support@bn-link.com
 Http://www.bn-link.com
 Hours: 9AM - 5PM PST, Mon - Fri
 Designed in California Made in China