

# **BN-LINK<sup>®</sup>**

## **SURGE PROTECTOR WITH 6 OUTLETS 3 USB CHARGING PORTS**



### **BN-LINK INC.**

12991 Leffingwell Avenue, Santa Fe Springs  
Customer Service Assistance: 1.909.592.1881

E-mail: [support@bn-link.com](mailto:support@bn-link.com)

[Http://www.bn-link.com](http://www.bn-link.com)

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China

## Specification

Rated Power: 1875W-15A MAX. 125V 60Hz

Combined USB Output Rating: 5V 3.4A

Individual USB Output Rating: 5V 2.4A


Joules rating: 600 Joules

Do not exceed the electrical rating.

Use only in dry places and indoors.

## Precautions

1. Please insert the plug completely into the outlets.
  2. Do not use this unit in damp or humid conditions.
  3. Do not use in receptacles that are not properly grounded.
  4. Please keep the unit out of reach of children.
  5. Use this product only with a 125 volt AC power source.
- Do not exceed 1875 watts and/or 15 amps maximum load.



- 1: ① refers to the product indicator, that is, when the product is powered on, the blue light is on, and when the power is off, the blue light is off.
- 2: ② refers to the TYPE-C output port, 5V 2.4A.
- 3: ③ refers to the USB-A output port, a total of 2, 5V 3.4A single port maximum 2.4A.
- 4: ④ refers to the product fixing screw. When the plug on the reverse side of the product is inserted into the wall socket, the product can be fixed to the wall socket with the screw to make the product more stable.
- 5: ⑤ refers to the AC output port, a total of 6.