

Function Description

- 7 indicators : ON, OFF, 2/4/6/8-hour countdown, dusk-dawn
- With output indicator
- Remote control range: 100 ft(open space)
- With overloading protector
- Light-sensitive photocell to operate
- Operating environment: for outdoor use



Input & Output Appearance

6x



Ratings & Approval

Outlet:

Voltage Compatibility: 125V AC

Frequency: 60Hz

Max. Load: 15A/1875W Resistive
10A/1250W Tungsten

Other Ratings: 1/2 HP

Remote Controller:

Wireless Frequency: 433.92 MHz

Battery Type: 12V 23A



Packing



Product Measurement (inch): 4.21×3.39×9.45

Product Weight (lb): 1.18

Unit Package Measurements (inch): 4.21×3.39×9.69

Unit Package Weight (lb): 1.52

Unit Package Measurements (inch): 4.21×3.39×9.45

Unit Package Weight (lb): 1.65

Master Carton Measurements (inch): 21.62×21.26×10.04

Master Carton Weight (lbs): 42.77

Master Carton Quantity: 30PCS

Master Carton Cube (cu.ft): 2.67

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730

Customer Service Assistance: 1.909.592.1881

E-mail: support@bn-link.com

Http://www.bn-link.com

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China