

Function Description

- With ON/Timer override switch
- Up to 24 On/Off programs daily
- Min. Setting: 30 minutes
- Max. Setting: 24 hours
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)



Input & Output Appearance

1x



Ratings & Approval

Voltage Compatibility: 125V AC**Frequency:** 60Hz**Max. Load:** 15A/1875W Resistive

8A/1000W Tungsten

Other Ratings: 1/2 HP, TV-5

Packing



Product Measurement (inch): 2.23×2.19×3.31

Product Weight (lb): 0.19

Unit Package Measurements (inch): 3.86×2.36×3.62

Unit Package Weight (lb): 0.44

Master Carton Measurements (inch): 19.88×12.99×8.90

Master Carton Weight (lbs): 23.61

Master Carton Quantity: 50 PCS

Master Carton Cube (cu.ft): 1.33

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730

Customer Service Assistance: 1.909.592.1881

E-mail: support@bn-link.com

Http://www.bn-link.com

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China