

### Function Description

- Large LCD display
- AM/PM clock display
- With output indicator
- Select the Timer1 outlet, or the Timer2 outlet, or both outlet controlled by same program
- Program: up to 8 ON/OFF programs can be set for either or both outlets; Min. Setting: 1 minute, Max. Setting: 7 days
- With Ni-MH rechargeable battery
- With Random function
- With daylight saving time option
- With key locking function
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)



### Input & Output Appearance

2x



### Ratings & Approval

**Voltage Compatibility:** 125V AC

**Frequency:** 60Hz

**Max. Load:** 15A/1875W Resistive

8A/1000W Tungsten

8A/1000W Ballast

**Other Ratings:** 1/2 HP, TV-5



### Packing



Product Measurement (inch): 3.25×2.81×3.34

Product Weight (lb): 0.37

Unit Package Measurements (inch): 3.58×3.03×3.78

Unit Package Weight (lb): 0.45

Master Carton Measurements(inch): 18.50×16.54×8.86

Master Carton Weight (lbs): 22.04

Master Carton Quantity: 50 PCS

Master Carton Cube (cu.ft): 1.57

**CENTURY PRODUCTS INC.**  
 3545 Granada Ave El Monte Ca 91731  
 Custom Service Assistance: 1.909.592.1881  
 E-mail: support@bn-link.com  
 Http://www.bn-link.com  
 Hours: 9AM - 5PM PST, Mon - Fri  
 Designed in California Made in Cambodia