

### Function Description

- Large LCD display
- AM/PM clock display
- With output indicator
- Select the Timer1 outlet, or the Timer2 outlet, or both outlet controlled by same program
- Program: up to 8 ON/OFF programs can be set for either or both outlets;
- Min. Setting: 1 minute, Max. Setting: 7 days
- With Ni-MH rechargeable battery
- With Random function
- With daylight saving time option
- With key locking function
- Operating environment: for indoor use only
- Operating Temperature: 14°F to 122°F (-10°C to 50°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)



### Input & Output Appearance

1X



### Ratings & Approval

**Voltage Compatibility:** 125V AC

**Frequency:** 60Hz

**Max. Load:** 15A/1875W Resistive  
8A/1000W Tungsten

**Other Ratings:** 1/2 HP, TV-5



### Packing



Product Measurement (inch): 2.87×2.56×5.08

Product Weight (lb): 0.3

Unit Package Measurements (inch): 2.87×2.56×5.08

Unit Package Weight (lb): 0.41

Master Carton Measurements(inch): 15.5×13.58×10.82

Master Carton Weight (lbs): 20.94

Master Carton Quantity: 50 PCS

Master Carton Cube (cu.ft): 1.32