

Function Description

- With timer function
- With ON/Timer switch knob
- Up to 48 On/Off programs daily
- Min. Setting: 15 minutes
- Max. Setting: 24 hours
- With Overload protector
- With grounded pin
- Operating environment: For outdoor use
- Operating Temperature: 14°F to 122°F (-10C to 50C)
- Storage Temperature: -4 °F to 140°F (-20C to 60C)



Input & Output Appearance

6x



Ratings & Approval

Voltage Compatibility : 125V AC

Frequency : 60Hz

Max. Load : 15A/1875W Resistive

15A/1875W Tungsten

Other Ratings: 1 HP,TV-5



Packing



Product Measurement (inch): 10.04×7.13×5.24

Product Weight (lb): 1.77

Unit Package Measurements (inch): 10.04×7.13×5.24

Unit Package Weight (lbs): 2.28

Master Carton Measurements (inch): 21.46×15.28×10.90

Master Carton Weight (lbs): 20.06

Master Carton Quantity: 8 PCS

Master Carton Cube (cu.ft): 2.07

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730
 Customer Service Assistance: 1.909.592.1881
 E-mail: support@bn-link.com
 Http://www.bn-link.com
 Hours: 9AM - 5PM PST, Mon - Fri
 Designed in California Made in China