

Short Period Repeat Cycle Timer BND-60/U97A

- Four operating modes Program repeats contin Program runs in day time only Program runs in night time only; - ON event duration: 5 seconds - 30 minutes - OFF event duration: 5 seconds - 60 minutes

- **Function Description**

Operating environment: for indoor use only
 Operating Temperatures: 5°F to 122°F (-15°C to 50°C)
 Storage Temperatures: -4°F to 140°F (-20°C to 60°C)



Input & Output

Appearance





1x -1

Voltage Compatibility: 125V AC

Frequency: 60Hz

Max. Load: 15A/1875W Resistive

15A/1875W Tungsten

15A/1875W Electronic Ballast





Packing



Product Measurement (inch): 3.27×2.44×4.76 Product Weight (lb): 0.3

Unit Package Measurements (inch): 3.27×2.44×4.76

Unit Package Weight (lb): 0.37

Master Carton Measurements (inch): 13.78×13.39×10.43 Master Carton Weight (lbs): 16.12 Master Carton Quantity: 40 PCS

Master Carton Cube (cu.ft): 1.11

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730
Customer Servico Assistance: 1,909,592,1881
E-mail: support@bh-link.com
Http://www.bh-link.com
Hours: 9AM - 5PM PST, Mon - Fri
Designed in California Made in China