



# Technical Data

PRODUCT TECH

©2019 TORCO

## T-2i 2-STROKE INJECTION OIL

### >>Description

Torco T-2i 2-Stroke Injection Oil is a combination of smokeless synthetic, highly refined low carbon petroleum base oils offering “ultra-clean” performance and protection in 2-cycle engines. A proprietary additive system virtually eliminates deposits under a full range of RPM and temperature conditions. T-2i’s clean combustion properties offer better throttle response, improved acceleration and increased power efficiency. T-2i is a popular choice for smaller displacement 2-cycle engines.

### >>Features

- >Synthetic blend technology
- >The most advanced low smoke performance
- >Improves power efficiency and throttle response
- >Excellent detergency for clean, deposit free operation
- >Reduced engine wear and provides excellent oxidation protection

### >>Application

For use in small air cooled and liquid cooled 2-cycle engines: motorcycle, scooter, moped, ATV and garden equipment applications.

Exceeds all manufacturer warranty requirements.

Exceeds: JASO-FC / ISO-L-EGD / API-TC

Designed for oil injection systems but can also be used in premix applications

### >>Typical/Test Data

<b>Description</b>	<b>ASTM#</b>	T-2i
<b>Appearance</b>	<b>Visual</b>	Clear/Green
<b>API Gravity</b>	<b>D-287</b>	32.1
<b>Lbs/Gal</b>	<b>Tables</b>	7.202
<b>Specific Gravity @ 15.6/15.6°C</b>	<b>D-1298</b>	0.8649
<b>Viscosity @ 100°C</b>	<b>D-445</b>	8.1
<b>Viscosity @ 40°C</b>	<b>D-445</b>	54
<b>Viscosity Index</b>	<b>D-2270</b>	118
<b>Pour Point, °C</b>	<b>D-97</b>	-35
<b>Flash Point, °C</b>	<b>D-93</b>	71
<b>Fire Point, °C</b>	<b>D-93</b>	92
<b>Calcium, % Weight</b>	<b>XRF</b>	0.025

### >>Directions

Use at full strength in injector systems. For best performance in premix applications, T-2i is recommended at ratios of 32:1 to 40:1.

### >>Package Sizes / P/N

<b>Description</b>	T-2i
<b>1-Liter (1.056 US QT)</b>	T920022CE
<b>12/1-Liter Case</b>	T920022C
<b>5 Gallon Pail</b>	T920022E
<b>55 Gallon Drum</b>	T920022B

