

# VFWF SERIES



**Pump fully stainless steel in AISI 304 material.**

**Motor thermal protection built -in type.**

**VSD drive unit and completed with (1 x 8L or 18L )  
Wave pressure tank.**

**Pressure sensor (1 x 10bar) & Built-in check valve.**

**Indoor installation Mode type  
(Option : Outdoor installation with sun & rain canopy)**

## Horizontal Multistage Centrifugal Stainless Steel Booster Pump

Pump Model	Motor [kW]	Specification	Duty Specification		Motor Type	Pressure Tank [Litres]	Connection	
			Capacity [m3/hr]	Head [meter]			Inlet	Outlet
VFWF-16/2-14	0.37	1/230/50	2	14	IE2	8	G 1 "	G 1 "
VFWF-16/2-21	0.37	1/230/50	2	21		8		
VFWF -16/2-28	0.55	1/230/50	2	28		8		
VFWF-16/2-35	0.55	1/230/50	2	35		8		
VFWF-16-/2-42	0.75	1/230/50	2	42		8		
VFWF-16/4-15	0.55	1/230/50	4	14	IE2	8	G1 1/4 "	G 1 "
VFWF-16/4-22	0.75	1/230/50	4	22		8		
VFWF-16/4-30	0.75	1/230/50	4	30		8		
VFWF-16/4-38	1.1	1/230/50	4	38		8		
VFWF-16/4-45	1.1	1/230/50	4	45		8		
VFWF-16/8-20	0.75	1/230/50	8	20	IE 2	18	G 2 "	G 1 1/2"
VFWF-16/8-26	1.1	1/230/50	8	26		18		
VFWF-16/8-36	1.85	1/230/50	8	36		18		
VFWF-16/8-43	2.2	1/230/50	8	43		18		
VFWF-16/8-48	2.2	1/230/50	8	48		18		
VFWF-16/12-20	1.5	1/230/50	12	20	IE 2	18	G 1 1/2"	G 1 1/2"
VFWF-16/12-28	1.85	1/230/50	12	28		18		
VFWF-16/12-33	2.2	1/230/50	12	33		18		
VFWF-16-12-39	2.2	1/230/50	12	39		18		
VFWF-16/16-20	1.5	1/230/50	16	20	IE 2	18	G 2"	G 2"
VFWF-16/16-30	2.2	1/230/50	16	30		18		
VFWF-16/20-10	1.0	1/230/50	20	10	IE 2	18	G 2"	G 2"
VFWF-16/20-20	1.85	1/230/50	20	20		18		

\* All specifications are subject to change without prior notice

# VFWC SERIES

**Pump fully stainless steel in AISI 304 material.**


**Motor thermal protection built-in type.**

**Pressurised booster unit and completed with automatic pressure controller (APC 1.5 or 2.2)**

**APC completed with built-in check valve.**

**Indoor installation Mode type**

**(Option : Outdoor installation with Sun & rain canopy)**



## Horizontal Multistage Centrifugal Stainless Steel Booster Pump

Pump Model	Motor [kW]	Specification	Duty Specification		Motor Type	Auto Pressure Controller	Connection	
			Capacity [m3/hr]	Head [meter]			Inlet	Outlet
VFWC-16/2-15	0.37	1/230/50	2	21	IE2	APC 1.5	G 1 "	G 1 "
VFWC-16/2-28	0.55	1/230/50	2	28		APC 2.2		
VFWC -16/2-35	0.55	1/230/50	2	35		APC 2.2		
VFWC-16/2-42	0.55	1/230/50	2	42		APC 2.2		
VFWC-16/4-15	0.55	1/230/50	4	15	IE2	APC 1.5	G1 1/4 "	G 1 "
VFWC-16/4-22	0.75	1/230/50	4	22		APC 1.5		
VFWC-16/4-30	0.75	1/230/50	4	30		APC 2.2		
VFWC-16/4-38	1.0	1/230/50	4	38		APC 2.2		
VFWC-16/4-45	1.1	1/230/50	4	45		APC 2.2		
VFWC-16/8-20	0.75	1/230/50	8	20	IE 2	APC 1.5	G 2 "	G 1 1/2"
VFWC-16/8-24	1	1/230/50	8	24		APC 2.2		
VFWC-16/8-27	1.5	1/230/50	8	27		APC 2.2		
VFWC-16/8-36	1.85	1/230/50	8	36		APC 2.2		

\* All specifications are subject to change without prior notice

**TURCOMP EMS SDN BHD**

No. 5, Jalan BP6/11, Bandar Bukit Puchong, 47100 Puchong, Selangor, Malaysia.  
Tel: +6 (03) 8060 6682 / 8060 6683 Fax: +6 (03) 8068 6689 Email : [ws-enquiry@turcomp.com](mailto:ws-enquiry@turcomp.com) Website : [www.turcomp.com](http://www.turcomp.com)