

INSTRUCTIONS



CITTERIO RIMLESS

2202.4

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- **Fitting:** Body made in aluminium with PVC housing.
Module: PVC body and Lens
- **Lamp types (module):**
1 x 10W 15° / 38° / 55° 3000K / 4000K
- **Protection against electric shock:** CLASS. II
- **Ingress Protection:** IP20. Protection against the entry of solid bodies with dimensions > 12mm. Not protected against water.
- **Ballast:** Includes LED driver.
- **Quality/Corrosive rating:** Suitable for indoor Installation only.
- **Ambient temperature range:** -20°C to +50°C.

INSTALLATION INSTRUCTIONS:

⚠ Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated



CAUTION: Risk of electric shock

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

- Ensure mains supply is switched off.
- Make a cut-out of Ø90mm diameter in the ceiling, leaving enough height for fitting H.120. (Fig.1)
- Remove the reflector and with 4 screws provided attach the body to the ceiling.(Fig.2)
- Connect the driver to the main supply using crimping ferrols. (Fig. 3)
Brown (Live) - to Brown or Red
Blue (Neutral) - to Blue or Black
- Connect with driver to the fitting (Fig.3)
- Connect the module to the reflector. (Fig.4)
- Install the fitting into the ceiling (Fig.5)
- Switch on mains supply.

WARNING:

- Ensure all items and screws are secure and fitted correctly.

