# **INSTRUCTIONS**

# **UNTOLD RECESSED DOWNLIGHT**

2206.33 2206.29 2206.21 2206.46

Please read the instructions before commencing installation and retain for future reference.

# **SPECIFICATIONS:**

- Fitting: Turned aluminumLamp types: 10W / Gu10
- Protection against electric shock: Class 1, requires earth connection
- Ingress Protection: IP20. Protection against the entry of solid bodies

greater than 12mm

- Ballast: Not required
- **Quality/Corrosive rating:** Suitable for domestic and commercial indoor applications.
- Ambient temperature range: -20°C to + 80°C.

#### INSTALLATION INSTRUCTIONS:



Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142.

On completion of installation, ensure that the Certificate of Compliance is updated.

### Ensure mains supply is switched off

- Cut the holes in the ceiling as per recommended cut-out size (Fig. 1)
- Connect the lamp holder to the mains supply via the terminal block provided on the lamp holder bracket (Fig. 2)
- Remove inner ring from the fitting. (Fig. 2)
- Fit lamp into lamp holder and fix into position with the inner ring (Fig 3 and 4).
- The Inner ring can be replaced with directional insert accessories.
- Insert the fitting into the cut out ensuring that the mains lead
- is not trapped. Push the mounting clips upwards to snap the fitting firmly into position, flush with the ceiling (Fig. 5).

## Switch on mains supply.

## **WARNING:**

- Ensure all items and screws are tight.
- Do not operate/install any product which appears damaged in any way.
- If damaged return the complete product to the place of purchase for inspection, repair or replacement.
- Ensure there are no components missing before commencing installation



