# **INSTRUCTIONS**

## LONE ADJ. SURFACE MOUNT

### 246606 246607

Please read the instructions before commencing installation and retain for future reference.

### **SPECIFICATIONS:**

- Fitting: Extruded aluminum housing
- · Lamp types:

246606: 10W / 230V / Gu10 246607: 2 x 10W / 230V / Gu10

- Protection against electric shock: CLASS I. Requires earth connection.
- **Ingress Protection:** IP20. Protection against the entry of solid bodies greater than 12mm.
- · Ballast: not required
- Quality/Corrosive rating: Suitable for commercial use and indoor applications.
- Ambient temperature range: -8°C to +55°C.

### **INSTALLATION INSTRUCTIONS:**

Electrical products can cause death, injury or damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



**CAUTION:** Risk of electric shock

### Ensure mains supply is switched off.

- Remove the ring and mounting base by screw driver, fix the mounting base on the ceiling. Feed the wire through the mounting base hole (Fig.1)
- Connect the fitting to its electrical source Brown (Live) - to Brown or Red Blue (Neutral) - to Blue or Black Green/Yellow (Earth) - to Green/Yellow or Copper. (Fig. 2)
- Re-attach the housing to the mounting base (Fig. 3)
- Install the lamp and fix back the ring: (Fig.4)

### Switch main supply back on.

#### WARNING:

- Ensure all items and screws are secure and fitted correctly.



