

# INSTRUCTIONS

## PORTICO SLIM LED

|                  |                  |
|------------------|------------------|
| 2847.25.10.30.31 | 2847.25.36.30.31 |
| 2847.25.10.40.31 | 2847.25.36.40.31 |
| 2847.25.10.30.30 | 2847.25.36.30.30 |
| 2847.25.10.40.30 | 2847.25.36.40.30 |

Please read the instructions before commencing installation and retain for future reference.

### SPECIFICATIONS:

- **Fitting:** Body made in aluminium with a tempered glass diffuser
- **Lamp types:**  
25W/230V LED Warm White 3000K  
25W/230V LED Natural White 4000K
- **Protection against electric shock:** CLASS I. Requires earth connection.
- **Ingress Protection:** IP40. Protection against the entry of solid bodies with dimensions > 1mm
- **Ballast:** Includes LED driver.
- **Quality/Corrosive rating:** Suitable for inland Installation, commercial use and indoor/outdoor applications.
- **Ambient temperature range:** -20°C to +45°C.

### INSTALLATION INSTRUCTIONS:

**⚠** Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.

Ensure mains supply is switched off.

- Determine mounting location and knock the plastic anchors into ceiling. Fix the round bracket with screws into the ceiling (Fig. 2)
- Connect the fitting to its electrical source using the terminal block provided  
Brown (Live) - to Brown or Red  
Blue (Neutral) - to Blue or Black  
Green/Yellow (Earth) - to Green/Yellow or Copper. (Fig. 3)  
Attach the body of the fitting to the ceiling bracket by rotating it clockwise (Fig. 4.)
- Turn on mains supply. (Fig. 5)

### WARNING:

- Ensure all items and screws are secure and fitted correctly.

