INSTRUCTIONS

DOLCE LED SPOT

4132.42.40.30.30 4132.42.40.30.31 4132.42.40.40.30 4132.42.40.40.31

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- Fitting: Aluminum body with glass diffuser.
- Lamp types: 42W / LED 3000K or 4000K
- Protection against electric shock: CLASS I requires earth connection.
- **Ingress Protection:** IP20.Protection against the entry of solid bodies with dimensions more than 12mm.
- Ballast: Includes LED Driver
- Quality/Corrosive Rating: Suitable for commercial use, Indoor except in corrosive environments.
- Ambient temperature range: -20° to +40°
- Maximum Protected Area: 0.20m×0.11m=0.22 m²

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury or damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.

Ensure mains supply is switched off.

- This fitting is track mounted, ensure that the track is powered by main supply correctly using the power feed accessory.
 Please note: Track and Power Feed are sold separately
- Mounting the Spot (Fig.1)
 Ensure that track adaptor is correctly and securely fitted into the mounting track before operating the fitting.
 - Step 1. Place the adapter into the track correctly
 - Step 2. Push the button to lock the adapter in place
- Adjust beam direction (Fig.2)
 - Tilting 0-80°
 - Horizontal: 0-355°

Please ensure that the track and power cable are installed according to the track installation instruction and that the fitting is securely attached to the track.

Switch on mains supply

WARNING: Please ensure that this fitting is earthed and that all items and screws are tight. The use of silicon sealer or the incorrect cable will void the warranty





