

INSTRUCTIONS

ANNA SQ

4510.211.30

4510.211.31



Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- **Fitting:** Plastic body with plastic diffuser
- **Lamp types:**
E27 GLS 240V 60W max.
- **Protection against electric shock:** CLASS II. Does not require earth connection.
- **Ingress Protection:** IP66 Complete protection against the entry of dust and big waves.
- **Driver:** Not Applicable
- **Application:** Suitable for coastal installation, commercial use, outdoor and indoor applications.
- **Ambient temperature range:** -20°C to +40°C.

INSTALLATION INSTRUCTIONS:

⚠ Electrical products can cause death, injury, damage to property.

Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142.

On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

Ensure mains supply is switched off.

- Using backplate as a template, mark position of mounting screws and main cable entry hole onto mounting surface. Note: If installing the eyelid type of fitting, ensure that mounting hole next to lampholder on backplate is positioned centrally at top so that eyelid is horizontal.
- Drill holes for mounting screws and mains cable entry.
- Insert masonry plugs into mounting holes.
- Bring mains cable through cable entry hole in mounting surface and Through cable entry grommet in backplate.
- Fix backplate onto mounting surface with screws.
- Connect mains cable to terminal block ensuring all connections are Tight.
- Fit lamp firmly into lampholder.
- Reassemble rim and diffuser to backplate with screws.
- Ensure sealing ring is correctly sealed in backplate.
Brown (Live) - to Brown or Red
Blue (Neutral) - to Blue or Black

Switch on the power supply and test the fitting

WARNING:

- Ensure all items and screws are secure and fitted correctly.

