INSTRUCTIONS

DUNE WALL UP/DOWN WALL LIGHT



4529/52 4529/31

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- **Fitting:** Body made in aluminium with white polycarbonate diffuser.
- Lamp types:

60W/15W 230V E27

- Protection against electric shock: CLASS I. Requires earth connection.
- **Ingress Protection:** IP54. Protection against the entry of dust and water splashes
- Ballast: not required.
- Quality/Corrosive rating: Suitable for indoor / outdoor domestic and commercial use.
- Ambient temperature range: -25°C to +55°C.

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142.

On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

Ensure main supply is switched off.

- Drill 2 holes in the wall and insert the expansion anchors. Install the base plate with the screws provided. (Fig. 1)
- Connect the fitting to its electrical source using the terminal block provided. (Fig. 2)

Brown (Live) - to Brown or Red

Blue (Neutral) - to Blue or Black

Green/Yellow (Earth) - to Green/Yellow or Copper.

- Install the lamp. (Fig. 3)
- Attach the body and diffuser to the base plate. (Fig. 4)
- Secure the body with the screws provided. (Fig. 5)

Turn on the mains supply.

WARNING: Ensure all items and screws are secure and fitted correctly.

