

INSTRUCTIONS



RYKA and ALCOR WALL LIGHT

UP AND DOWN

RYKA: 4531.1.30 4431.1.31
ALCOR: 4531.3.30 4531.3.31

DOWN

4531.2.30 4531.2.31
4531.4.30 4531.4.31

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- **Fitting:** Body made in polycarbonate & abs with Polycarbonate diffuser.
- **Lamp types:**
4531.1/4531.3: 2 x GU10/230V
4531.2/4531.4: 1 x GU10/230V
- **Protection against electric shock:** CLASS II.
- **Ingress Protection:** IP65. Complete protection against dust and against the effects of water jets.
- **Quality/Corrosive rating:** Suitable for outdoor/indoor commercial use.
- **Ambient temperature range:** -20°C to +55°C.

INSTALLATION INSTRUCTIONS:

⚠ Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

- Switch off mains supply and unscrew the base. (Fig.1).
- Remove the body and open the lamp cover. (Fig.2/Fig.3)
- Feed the main supply cable through the grommet in the base and fix the base on the wall (Fig.4)
- Connect the main cable to the terminal block provided and ensure the correct connection as marked. (Fig.5):
Brown(Live) -to Brown or Red
Blue(Neutral) – to Blue or Black
- Re-attach the lamp body with the base. (Fig.6/Fig.7)
- Insert a suitable LED lamp/s and ensure the wattage does not exceed that marked on the label. (Fig.8).
- Re-attach the lamp cover and turn on the power. (Fig.9)

PLEASE NOTE: Never look directly into the LED

WARNING: Ensure all items and screws are secure and fitted correctly.

