INSTRUCTIONS

RAZOR WALL LIGHT

4548, 3030 4548, 3031 4548, 4030 4548, 4031

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS

- Fitting: Body made in polycarbonate & ABS with polycarbonate diffuser.
- Lamp types:

4548: 5.4W / 230V / LED 3000 or 4000K

- Protection against electric shock: CLASS II.
- **Ingress Protection:** IP65. Complete protection against dust and against the effects of water jets.
- **Quality/Corrosive rating:** Suitable for outdoor / indoor commercial and domestic applications
- Ambient temperature range: -20°C to +45°C.

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

Ensure main supply is switched off. • Remove the lamp cover. (Fig. 1).

- Unscrew the mounting bracket on the PC diffuser. (Fig.2)
- Feed the main supply cable through the grommet of the mounting bracket and fix it to the wall (Fig.3 / 4)
- Connect the main cable to the terminal block provided and ensure correct connection as marked.(Fig.5):
 Brown(Live) - to Brown or Red
 Blue(Neutral) - to Blue or Black
- Re-attach the mounting bracket securely to the diffuser. (Fig.6)
- Re-attach the lamp cover (Fig.7 / 8)

Switch on mains supply

WARNING: Ensure all items and screws are secure and fitted correctly.



RAZOR WALL LIGHT

