## **INSTRUCTIONS**

### **BLOCK P WALL LIGHT**

4556.1.30	4556.1.31	4556.1.50
4556.2.30	4556.2.31	4556.2.50

Please read the instructions before commencing installation and retain for future reference.

#### SPECIFICATIONS:

- **Fitting:** Body made in polycarbonate & ABS with Polycarbonate diffuser.
- Lamp types: 4556.1: 10W / 230V / GU10 LED 4556.2: 2 x 10W / 230V / GU10 LED
- Protection against electric shock: CLASS II.
- Ingress Protection: IP54. Protection against dust and against the effects of water jets.
- **Quality/Corrosive rating:** Suitable for outdoor/indoor commercial use.
- Ambient temperature range: -20°C to +45°C.

## INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

#### Switch of mains supply

- Remove the lamp cover. (Fig.1 and 2).
- Feed the main supply cable through the grommet in the mounting bracket and fix it to the wall (Fig.3)
- Connect the main cable to the terminal block provided and ensure the correct connection as marked.(Fig.4): Brown(Live) -- to Brown or Red Blue(Neutral) -- to Blue or Black
- Insert a suitable LED lamp/s and ensure the wattage does not exceed that marked on the label. (Fig.5).
- Re-attach the lamp cover (Fig.6)

#### Switch on mains supply

WARNING: Ensure all items and screws are secure and fitted correctly.

Spazio Lighting (Pty) LTD. JOHANNESBURG OFFICE: 52 Andries Street | Wynberg/Sandton CAPE TOWN OFFICE: 36 Milner Street | Paarden Eiland DURBAN OFFICE: 31 Solstice Road | Umhlanga Ridge 011 555 5555 (Central Switchboard) | info@spazio.co.za

# BLOCK P WALL LIGHT



