INSTRUCTIONS

RUBIK WALL

4560.01.30 4560.02.30

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

Fitting: Body made in stainless steel with:

4560.01: Clear Glass Diffuser 4560.02: Opal Glass Diffuser

Lamp types: 230V / E27

 Protection against electric shock: CLASS I. Requires earth connection.

 Ingress Protection: IP44. Protection against the entry of solid bodies greater than 1mm. Protection against water sprays.

• Ballast: Not required

 Quality/Corrosive rating: Suitable for indoor / outdoor domestic and commercial use.

• Ambient temperature range: -25°C to +55°C.

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 60598-1:2014

On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

Ensure main supply is switched off.

- ` Unscrew and remove the base. (Fig. 1)
- Connect the main cable to the terminal block provided and ensure correct connection as marked. (Fig. 2)
 Brown (Live) - to Brown or Red
 Blue (Neutral) - to Blue or Black
 Green/Yellow (Earth) - to Green or copper
- Drill 4 holes in the wall and insert the expansion anchors.
 Attach the base with the screws provided. (Fig. 3)
- Insert the lamp and re-attach the body to the base. (Fig. 4)

Turn on the mains supply.

WARNING: Ensure all items and screws are secure and fitted correctly.









