

# INSTRUCTIONS

## RUBIK LONG WALL



4561.01.30

Please read the instructions before commencing installation and retain for future reference.

### SPECIFICATIONS:

- **Fitting:** Body made in 201 stainless steel with tempered clear glass.
- **Lamp types:** 2 x 230V / E27
- **Protection against electric shock:** CLASS I. Requires earth connection.
- **Ingress Protection:** IP44. Protection against the entry of solid bodies greater than 1mm and water sprays.
- **Driver:** Not applicable
- **Quality/Corrosive rating:** Suitable for indoor / outdoor domestic and commercial use.
- **Ambient temperature range:** -25°C to +55°C.

### INSTALLATION INSTRUCTIONS:

**⚠** Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 60598-1:2014. On completion of installation, ensure that the Certificate of Compliance is updated.



**CAUTION:** Risk of electric shock

**PLEASE NOTE:** This fitting can be installed both horizontally and vertically. Please ensure drain holes lie at the bottom of the fitting whether installed vertically or horizontally. (Fig. 1)

**Ensure mains supply is switched off.**

- Unscrew and remove the base. (Fig. 1)
- Connect the main cable to the terminal block provided and ensure correct connection as marked. (Fig. 2)  
Brown (Live) - to Brown or Red  
Blue (Neutral) - to Blue or Black  
Green/Yellow (Earth) - to Green or copper
- Drill 4 holes in the wall and insert the expansion anchors. Attach the base with the screws provided. (Fig. 3)
- Insert the lamp and re-attach the body to the base. (Fig. 4)

**Turn on the mains supply.**

**WARNING:** Ensure all items and screws are secure and fitted correctly.

