

INSTRUCTIONS



RUBIK OUT WALL

4562.30

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- **Fitting:** Body made in 201 stainless steel with tempered clear glass
- **Lamp types:** 230V / E27
- **Protection against electric shock:** CLASS I. Requires earth connection.
- **Ingress Protection:** IP44. Protection against the entry of solid bodies greater than 1mm and protection against water sprays.
- **Driver:** Not applicable
- **Quality/Corrosive rating:** Suitable for indoor / outdoor domestic and commercial use.
- **Ambient temperature range:** -25°C to +55°C.

INSTALLATION INSTRUCTIONS:

⚠ Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 60598-1:2014. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

Ensure mains supply is switched off.

- Unscrew and remove the base. (Fig. 1)
- Connect the main cable to the terminal block provided and ensure correct connection as marked. (Fig. 2)
Brown (Live) - to Brown or Red
Blue (Neutral) - to Blue or Black
Green/Yellow (Earth) - to Green or copper
- Drill 2 holes in the wall and insert the expansion anchors. Attach the base with the screws provided. (Fig. 3)
- Insert the lamp and re-attach the body to the base. (Fig. 4)

Turn on the mains supply.

WARNING: Ensure all items and screws are secure and fitted correctly.

