



- Slimline LED floodlight
- Slimline LED floodlight (Fig. 1)
  Modified polycarbonate body with aluminium inside
  Tempered glass diffuser
  304 Stainless steel bracket,
  Adjustable (Fig. 2)

- **10 30W** 10-30W LED
   Raw lumen: 1170 3510Lm

- 50W LEDRaw lumen: 5500Lm

- **100W** 100W LED
   Raw lumen: 12000Lm
- Natural white 4000K or Warm White 3000K (50W)
  110° Beam (Fig. 3)
  Includes LED driver
  Class I
  IP 65
  Coastal quality

Slimmer Design compared to a standard LED flood









Fig. 2





Code	Description	Kelvin / Lumen		
Iplast 2 10W 4648.1040.30	10W / LED	4000K	1170 lm	H 108
			□ 10W     LED	



To leave the second second leave the second second leave the second second leave the second s							
Code	Description	Kelvin / Lumen					
Iplast 2 20W 4648.2040.30	20W / LED	4000K	2340 lm	[] [8] <u>8</u>			
			⇒ 20W LED				







P 45 COASTAL QUALITY OF 90°							
Code	Description	Kelvin / Lumen					
Iplast 50W 4645.02.50.30.30 4645.02.50.40.30	50W / LED 50W / LED	3000K 4000K	5500 lm	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			
			⇒ 50W LED				







