INSTRUCTIONS

ICE WALL

5279

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- Fitting: Body made in stainless steel with opal glass diffuser.
- Lamp types: 6W / 3000K / LED
- Protection against electric shock: CLASS I. Requires earth connection.
- Ingress Protection: IP44. Protection against the entry of solid bodies greater than 1mm, Protection against water spravs.
- Ballast: Includes integral LED driver.
- Quality/Corrosive rating: Suitable for indoor applications.
- Ambient temperature range: -8°C to +55°C.

INSTALLATION INSTRUCTIONS:



Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS

10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualifiedperson.

Switch off mains supply.

- Remove the mounting bracket and fix it to the wall. (Fig. 1)
- Connect the fitting to its electrical source using the terminal block provided. (Fig. 2) Brown (Live) - to Brown or Red
 - Blue (Neutral) to Blue or Black


Green/Yellow (Earth) - to Green/Yellow or Copper.

- Fix the base to the wall bracket. (Fig. 3)
- Attach the glass shade. (Fig. 4)

Switch on mains supply

WARNING:

- Ensure all items and screws are secure and fitted correctly.



Spazio Lighting (Pty) LTD. JOHANNESBURG OFFICE: 52 Andries Street | Wynberg/Sandton CAPE TOWN OFFICE: 36 Milner Street | Paarden Eiland DURBAN OFFICE: 31 Solstice Road | Umhlanga Ridge 011 555 5555 (Central Switchboard) | info@spazio.co.za

SPAZIOF