
INSTRUCTIONS

MINI LED STRIPLIGHT

4W: 7039.04.30.31 7W: 7039.07.30.31 3000K 13W: 7039.13.30.31 18W: 7039.18.30.31 3000K

7039.13.30.31 18W: 7039.18.30.31 3000l



SPECIFICATIONS:

-Fitting: PC body and diffuser.

-Lamp types: 4W / LED

7W / LED 13W / LED 18W / LED

Protection against electric shock: CLASS I.

Ingress Protection: IP20. Protection against the entry of solid

bodies with dimensions of more than 12mm

Ballast: Includes LED driver.

Quality/Corrosive rating: Suitable for indoor, except in corrosive

environments

Ambient temperature range: -10°C to +45°C.

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. Please operate strictly according to the instruction don't modify the product randomly, only for indoor use. On completion of installation, ensure that the Certificate of Compliance is updated.

Ensure mains supply is switched off.

- Remove the clip on the wood or on the wall. (Fig. 1)
- Tighten the clips with screws. (Fig. 2)
- Mount the fitting on the clips (Fig. 3)
- Plug in the power cord, Switch on mains, fixtures can be connected is series, max 12pcs (Fig. 4)

WARNING:

It is suitable for stable wall or wooden surface.

Do not use the lamp in a high temperature or humid area in order to avoid lamp damage. The lamp is not designed for dimmer. LED lighting source, do not stare at the lights for long time. Do not open the product, as the led lighting source is irreplaceable.



