

3W




350mA

- Pri: 220-240V~50/60Hz 0.08A
- Sec: 350mA, 2.5 - 10.5V
- Operating Temp: -5°~+50°C
- Thermal Cut out: 75°C
- Class II

700mA

- Pri: 220-240V~50/60Hz 0.8A
- Sec: 700mA, 2.8 - 10.5V
- Operating Temp: -5°~+50°C
- Thermal Cut out: 75°C
- Class II




CODE	DESCRIPTION	PACKAGING
7317.350.03	3W/350mA	100 pcs/ctn
7317.700.03	3W/700mA	100 pcs/ctn

6W



- Pri: 220-240V~50/60Hz 0.06A
- Sec: 350mA, 9-18V
- Operating Temp: -20°~+50°C
- Thermal Cut out: 85°C
- Class II
- IP20




CODE	DESCRIPTION	PACKAGING
7317.350.06	6W/350mA	100 pcs/ctn

12W



- Pri: 220-240V~50/60Hz 0.1A
- Sec: 350mA, 2-34V
- Operating Temp: -20°~+50°C
- Thermal Cut out: 85°C
- Class II
- IP20

- Pri: 220-240V~50/60Hz 0.09A
- Sec: 700mA, 2-17V
- Operating Temp: -20°~+50°C
- Thermal Cut out: 85°C
- Class II
- IP20




CODE	DESCRIPTION	PACKAGING
7317.350.12	12W/350mA	100 pcs/ctn
7317.700.12	12W/700mA	100 pcs/ctn

20W



- Pri: 220-240V~50/60Hz 0.14A
- Sec: 350mA, 2-58V
- Operating Temp: -20°~+50°C
- Thermal Cut out: 85°C
- Class II
- IP20

- Pri: 220-240V~50/60Hz 0.14A
- Sec: 700mA, 2-29V
- Operating Temp: -20°~+50°C
- Thermal Cut out: 85°C
- Class II
- IP20




CODE	DESCRIPTION	PACKAGING
7317.350.20	20W/350mA	100 pcs/ctn
7317.700.20	20W/700mA	100 pcs/ctn

DIMMABLE CONSTANT CURRENT



10W

- Pri: 220-240V~50/60Hz 0.08A
- Sec: 260mA, 29-46V
- Operating Temp: -20°~+50°C
- Thermal Cut out: 80°C
- Dimmable on leading or trailing edge
- Class II
- IP20




CODE	DESCRIPTION	PACKAGING
7317.180.10.D	10W/260mA	100 pcs/ctn



18W

- Pri: 220-240V~50/60Hz 0.11A
- Sec: 350mA, 15-52V
- Operating Temp: -20°~+50°C
- Thermal Cut out: 90°C
- Dimmable on leading or trailing edge
- Class II
- IP20




CODE	DESCRIPTION	PACKAGING
7317.350.18.D	18W/350mA	100 pcs/ctn



30W

- Pri: 220-240V~50/60Hz 0.25A
- Sec: 350mA, 50-75V
- Operating Temp: -20°~+45°C
- Thermal Cut out: 85°C
- Dimmable on trailing edge
- Class II
- IP20



CODE	DESCRIPTION	PACKAGING
7317.350.30.D	30W/350mA	50 pcs/ctn



80W

- Pri: 220-240V~50/60Hz 0.4A
- Sec: 350mA, 30V
- Operating Temp: -25°~+50°C
- Thermal Cut out: 85°C
- Includes Dip switch
- Class II
- IP20



CODE	DESCRIPTION	PACKAGING
TC/122214	80W/350mA	1 pc/ctn



80W

- Pri: 220-240V~50/60Hz 0.4A
- Sec: 220-500mA, 30-210V
- Operating Temp: -25°~+50°C
- Thermal Cut out: 85°C
- Includes Dip switch and Dali dimmer
- Class II
- IP20



CODE	DESCRIPTION	PACKAGING
TC/127086	80W/500mA	1 pc/ctn