




### STR 50 SAFETY TRANSFORMER

- Pri: 220-240V~50/60Hz
- Sec: 11.5V, 3.95A
- Operating Temp: -10°~+40°C
- Thermal Cutout: 80°C
- Class I
- IP20
- Dimmable: Leading and Trailing edge




| CODE | DESCRIPTION | PACKAGING  |
|------|-------------|------------|
| 7301 | 20-50W/VA   | 20 pcs/ctn |



### PRECISE DIMMABLE TRANSFORMER

- Pri: 220-240V~50/60Hz 0.26A
- Sec: 11.5V, 0.5A
- Operating Temp: -10°~+50°C
- Thermal Cutout: 80°C
- Class II
- IP20
- Dimmable: Leading and Trailing edge




| CODE | DESCRIPTION | PACKAGING   |
|------|-------------|-------------|
| 7373 | 20-50W/VA   | 100 pcs/ctn |



### METAL HALIDE MAGNETIC GEAR

- Pri: 220-240V~50Hz
- Operating Temp: -10°~+40°C
- Class I
- IP20




| CODE      | DESCRIPTION    | PACKAGING |
|-----------|----------------|-----------|
| 7330/PLUG | 35W/230V 0.22A | 6 pcs/ctn |
| 7331/PLUG | 70W/230V 0.37A | 6 pcs/ctn |
| 7332/PLUG | 150W/230V 0.7A | 6 pcs/ctn |



### FLUORESCENT MAGNETIC GEAR

- Pri: 220-240V~50Hz
- Operating Temp: -10°~+40°C
- Class I
- IP20




| CODE     | DESCRIPTION  | PACKAGING |
|----------|--------------|-----------|
| 7322-IMP | 18W/230V     | 4 pcs/ctn |
| 7324-IMP | 2 x 13W/230V | 4 pcs/ctn |
| 7325-IMP | 2 x 18W/230V | 4 pcs/ctn |
| 7326-IMP | 2 x 26W/230V | 4 pcs/ctn |



### FLUORESCENT ELECTRONIC GEAR

- Pri: 220-240V~50/60Hz
- Operating Temp: -15°~+50°C
- Thermal Cut out: 75°C
- Class I
- IP20



| CODE       | DESCRIPTION                | PACKAGING  |
|------------|----------------------------|------------|
| 7327.1.218 | 2 x 18W/230V No Cabtyre    | 50 pcs/ctn |
| 7327.2.218 | 2 x 18W/230V Incl. Cabtyre | 40 pcs/ctn |
| 7327.2.226 | 2 x 26W/230V Incl. Cabtyre | 40 pcs/ctn |