INSTRUCTIONS

UFO LED HIGHBAY

7812.100.41.30.D

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- Fitting: Body made in aluminum and polycarbonate lens
- Lamp types: LED 100W 4000K 100-305V
- Protection against electric shock: CLASS I. Requires earth connection.
- Ingress Protection: IP65
- Ballast: Includes 1-10V Dimmable LED driver
- **Quality/Corrosive rating:** Suitable for commercial use and indoor/outdoor applications.
- Ambient temperature range: -25°C to +55°C.

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock.

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

Turn off mains supply

- Screw the circular ring tightly. Ensure that the installation surface is strong enough to carry 30kg. (Fig. 1)
- Hang the safety chain on the hook. (Fig. 2)
- Lock the circular ring to the safety Chain carefully. (Fig. 3)
- Connect the fitting to its electrical source (Fig. 3)
 Brown (Live) to Brown or Red
 Blue (Neutral) to Blue or Black
 Green/Yellow (Earth) to Green/Yellow or Copper.
 - 1-10V Switch control required for dimming.
- · Turn on mains supply and test fitting.

WARNING:

- Ensure all items and screws are secure and fitted correctly.



